

Lumen Tech

Lighting, LLC.

The *STEALTH* Design PMKH

Architectural Area Luminaire
Maximum 1000 Watt Metal Halide
Or High Pressure Sodium

Specifications

Housing: Heavy duty cast aluminum. Bronze powder coated finish. See finish note.

Lens: High impact/heat resistant tempered flat glass lens silicone sealed to door frame.

Reflector: Anodized aluminum, computer designed in conjunction with the lens for efficiency. 150W — 175W Type III distribution. 250W — 1000W Adjustable type II, type III or type IV distribution.

Ballast: Pre-wired C.W.A., H.P.F. core and coil with capacitor.

Lamp: Clear medium base 150W-175W, mogul base 250W-1000W lamp, (by others).

Lamp Holder: High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact.

Finish: Bronze, detergent cleaned, prime coated. Chip resistant powder urethane polyester coating.

Photometric Information: Contact factory.

Labels: U/L, CUL listed suitable for wet location.



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Ordering Information

Catalog Number	Watts	Light Source
PMKH150H	150	HPS
PMKH250H	250	HPS
PMKH400H	400	HPS
PMKH1000H	1000	HPS
PMKH150M	150	MH
PMKH175M	175	MH
PMKH250M	250	MH
PMKH250MP	250	MH PS
PMKH320MP	320	MH PS
PMKH350MP	350	MH PS
PMKH400M	400	MH
PMKH400MP	400	MH PS
PMKH1000M	1000	MH



KHRP Round Pole Adapter



KHWM Wall Mount Adapter



KHPC Photocell Adapter