

Lumen Tech

Lighting, LLC.

Design QGLT

16" Diameter Open Acrylic Refractor
Compact Fluorescent
Up To (4) PLT42W Lamps

Specifications

Housing: Heavy duty die cast aluminum construction with corrosion resistant hardware and mounting hook. See finish note.

Refractor: Injection molded prismatic acrylic. Provides brightness control, designed for maximum efficiency.

Ballast: Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

Lamp: PLT lamp, 4 pin base (by others) see ordering information.

Lamp Holder: White thermoplastic with snap-in lamp retainer springs.

Finish: Silver, detergent cleaned, prime coated. Chip resistant powder urethane polyester coating, electrostatic applied and baked.

Photometric Information: Contact factory.

Labels: U/L, CUL listed suitable for damp location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



Ordering Information

Open Aperture Fixtures

Catalog Number	Watts	Lamp Base
QGLT4T26	4-PLT26	GX24q-3
QGLT4T32	4-PLT32	GX24q-3
QGLT4T42	4-PLT42	GX24q-4
QGLT1T57	1-PLT57	GX24q-4

Options Suffix Catalog Number With

- F Flat Acrylic Lens
- A Dropped Acrylic Refractor



Easy hang quick surface mount bracket for one person installation allows two hands free for wiring.