

Lumen Tech

Lighting, LLC.

Design QSC15 Constellation Series Wall Sconce

Maximum 175W Metal Halide
150W High Pressure Sodium
Or 2-42W PLT Compact Fluorescent

Specifications

Housing: Heavy duty cast aluminum with quick mount system. Powder coated finish. See finish note.

Lens: Clear tempered glass silicone sealed to door frame.

Reflector: Anodized aluminum, computer designed for efficiency, [classified full cut-off dark sky compliant](#).

Ballast: **H.I.D.:** Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF:** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

Lamp: **H.I.D.:** Clear medium base. **CF:** PLT lamp, 4 pin base (by others).

Lamp Holder: **H.I.D.:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact.

CF: White thermoplastic with snap-in lamp retainer springs.

Finish: Bronze, detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

Photometric Information: Contact factory.

Labels: U/L, CUL listed suitable for wet location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



Ordering Information

Catalog Number	Watts	Light Source
QSC15T26	26	Compact Fluorescent
QSC15T32	32	Compact Fluorescent
QSC15T42	42	Compact Fluorescent
QSC15T226	2-26	Compact Fluorescent
QSC15T232	2-32	Compact Fluorescent
QSC15T242	2-42	Compact Fluorescent
QSC1550H	50	HPS
QSC1570H	70	HPS
QSC15100H	100	HPS
QSC15150H	150	HPS
QSC1550M	50	MH
QSC1570M	70	MH
QSC15100M	100	MH
QSC15150M	150	MH
QSC15175M	175	MH



Trunion mount option order catalog# **QSC15TR.**



Wireguard option order catalog# **QSC15WG.**



Polycarbonate shield option order catalog# **QSC15PS.**