

Lumen Tech

Lighting, LLC.

Design AL21

Surface Mount Area Light
Maximum 175 Watt Metal Halide
150W High Pressure Sodium
Or 2-42W PLT Compact Fluorescent
With 1/2" Hole For Optional Photo Cell

Specifications

Housing: High impact polycarbonate lens and housing with silicone gasket, finished bronze.

Reflector: Anodized aluminum, computer designed in conjunction with the lens for efficiency.

Ballast HID: Pre-wired H.P.F. core and coil with capacitor. **CF:** Compact fluorescent electronic high power factor class P, universal voltage 120V—277V 50 / 60 Hz.

Lamp HID: Clear medium base lamp. **CF:** PL max 2-13W. (by others).

Lamp Holder HID: High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** White thermoplastic with snap-in lamp retainer springs.

Photometric Information: Contact factory.

Labels: U/L, listed suitable for wet location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



Ordering Information

Catalog Number	Watts	Light Source
AL21T26	26	Compact Fluorescent
AL21T32	32	Compact Fluorescent
AL21T42	42	Compact Fluorescent
AL21T226	2-26	Compact Fluorescent
AL21T232	2-32	Compact Fluorescent
AL21T242	2-42	Compact Fluorescent
AL2170H	70	HPS
AL21100H	100	HPS
AL21150H	150	HPS
AL2170M	70	MH
AL21100M	100	MH
AL21150M	150	MH
AL21175M	175	MH

