

Lumen Tech

Lighting, LLC.

Design BEGD

6" Diameter 24", 36" or 42" Tall Dome Top Bollard
With White Polycarbonate Lens and Lens Guard

Specifications

Housing: Aluminum 6" diameter, fastened to a cast aluminum base with three countersunk stainless steel screws. See finish note.

Housing Top: Spun aluminum 6" diameter with a dome top. Finished same as housing.

Base: Cast aluminum, finished same as housing. See finish note.

Lens: Injection molded, 6" diameter, 1/4" thick white polycarbonate.

Ballast: **H.I.D.** Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

Lamp: **H.I.D.** Clear medium base. **CF** PLT lamp max. 42W, 4 pin base (by others).

Lamp Holder: **H.I.D.:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** White thermoplastic with snap-in lamp retainer springs.

Finish: Black, detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

Photometric Information: Contact factory.

Labels: U/L listed. Suitable for wet location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Ordering Information

Catalog Number	Height	Watts	Light Source
BEGD24T26	24"	26	Compact Fluorescent
BEGD24T32	24"	32	Compact Fluorescent
BEGD24T42	24"	42	Compact Fluorescent
BEGD2450H	24"	50	HPS
BEGD2470H	24"	70	HPS
BEGD2439M	24"	39	MH
BEGD2450M	24"	50	MH
BEGD2470M	24"	70	MH
BEGD36T26	36"	26	Compact Fluorescent
BEGD36T32	36"	32	Compact Fluorescent
BEGD36T42	36"	42	Compact Fluorescent
BEGD3650H	36"	50	HPS
BEGD3670H	36"	70	HPS
BEGD3639M	36"	39	MH
BEGD3650M	36"	50	MH
BEGD3670M	36"	70	MH
BEGD42T26	42"	26	Compact Fluorescent
BEGD42T32	42"	32	Compact Fluorescent
BEGD42T42	42"	42	Compact Fluorescent
BEGD4250H	42"	50	HPS
BEGD4270H	42"	70	HPS
BEGD4239M	42"	39	MH
BEGD4250M	42"	50	MH
BEGD4270M	42"	70	MH

