

# Lumen Tech

Lighting, LLC.

## Design BELD

6" Diameter 24", 36" or 42" Tall Dome Top Bollard  
Polycarbonate Lens With External Louver

### Specifications

**Housing:** Aluminum 6" diameter, fastened to a cast aluminum base with three countersunk stainless steel screws. See finish note.

**Housing Top:** Spun aluminum 6" diameter with a dome top. Finished same as housing.

**Base:** Cast aluminum, finished same as housing. See finish note.

**Lens:** Injection molded, 6" diameter, 1/4" thick clear polycarbonate.

**Ballast: H.I.D.** Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

**Lamp: H.I.D.** Clear medium base. **CF** PLT lamp max. 42W, 4 pin base (by others).

**Lamp Holder: H.I.D.:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** White thermoplastic with snap-in lamp retainer springs.

**Finish:** Black, detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

**Photometric Information:** Contact factory.

**Labels:** U/L listed. Suitable for wet location.

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE*

### Ordering Information

Catalog Number	Height	Watts	Light Source
BELD24T26	24"	26	Compact Fluorescent
BELD24T32	24"	32	Compact Fluorescent
BELD24T42	24"	42	Compact Fluorescent
BELD2450H	24"	50	HPS
BELD2470H	24"	70	HPS
BELD2439M	24"	39	MH
BELD2450M	24"	50	MH
BELD2470M	24"	70	MH
BELD36T26	36"	26	Compact Fluorescent
BELD36T32	36"	32	Compact Fluorescent
BELD36T42	36"	42	Compact Fluorescent
BELD3650H	36"	50	HPS
BELD3670H	36"	70	HPS
BELD3639M	36"	39	MH
BELD3650M	36"	50	MH
BELD3670M	36"	70	MH
BELD42T26	42"	26	Compact Fluorescent
BELD42T32	42"	32	Compact Fluorescent
BELD42T42	42"	42	Compact Fluorescent
BELD4250H	42"	50	HPS
BELD4270H	42"	70	HPS
BELD4239M	42"	39	MH
BELD4250M	42"	50	MH
BELD4270M	42"	70	MH

