

Lumen Tech

Lighting, LLC.

Design BELF

6" Diameter 24", 36" or 42" Tall Flat Top Bollard
Polycarbonate Lens With External Louver

Specifications

Housing: Aluminum 6" diameter, fastened to a cast aluminum base with three countersunk stainless steel screws. See finish note.

Housing Top: Spun aluminum 6" diameter with a radius edge. Finished same as housing.

Base: Cast aluminum, finished same as housing. See finish note.

Lens: Injection molded, 6" diameter, 1/4" thick clear polycarbonate.

Ballast: **H.I.D.** Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

Lamp: **H.I.D.** Clear medium base. **CF** PLT lamp max. 42W, 4 pin base (by others).

Lamp Holder: **H.I.D.:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** White thermoplastic with snap-in lamp retainer springs.

Finish: Black, detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

Photometric Information: Contact factory.

Labels: U/L listed. Suitable for wet location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Ordering Information

| Catalog Number | Height | Watts | Light Source |
|----------------|--------|-------|---------------------|
| BELF24T26 | 24" | 26 | Compact Fluorescent |
| BELF24T32 | 24" | 32 | Compact Fluorescent |
| BELF24T42 | 24" | 42 | Compact Fluorescent |
| BELF2450H | 24" | 50 | HPS |
| BELF2470H | 24" | 70 | HPS |
| BELF2439M | 24" | 39 | MH |
| BELF2450M | 24" | 50 | MH |
| BELF2470M | 24" | 70 | MH |
| BELF36T26 | 36" | 26 | Compact Fluorescent |
| BELF36T32 | 36" | 32 | Compact Fluorescent |
| BELF36T42 | 36" | 42 | Compact Fluorescent |
| BELF3650H | 36" | 50 | HPS |
| BELF3670H | 36" | 70 | HPS |
| BELF3639M | 36" | 39 | MH |
| BELF3650M | 36" | 50 | MH |
| BELF3670M | 36" | 70 | MH |
| BELF42T26 | 42" | 26 | Compact Fluorescent |
| BELF42T32 | 42" | 32 | Compact Fluorescent |
| BELF42T42 | 42" | 42 | Compact Fluorescent |
| BELF4250H | 42" | 50 | HPS |
| BELF4270H | 42" | 70 | HPS |
| BELF4239M | 42" | 39 | MH |
| BELF4250M | 42" | 50 | MH |
| BELF4270M | 42" | 70 | MH |

