

Lumen Tech

Lighting, LLC.

Design BILF

6" Diameter 24", 36" or 42" Tall Flat Top Bollard
Polycarbonate Lens With Internal Louver

Specifications

Housing: Aluminum 6" diameter, fastened to a cast aluminum base with three countersunk stainless steel screws. See finish note.

Housing Top: Spun aluminum 6" diameter with a radius edge. Finished same as housing.

Base: Cast aluminum, finished same as housing. See finish note.

Lens: Injection molded, 6" diameter, 1/4" thick clear polycarbonate.

Ballast: H.I.D. Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

Lamp: H.I.D. Clear medium base. **CF** PLT lamp max. 42W, 4 pin base (by others).

Lamp Holder: H.I.D.: High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** White thermoplastic with snap-in lamp retainer springs.

Finish: Black, detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

Photometric Information: Contact factory.

Labels: U/L listed. Suitable for wet location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Ordering Information

Catalog Number	Height	Watts	Light Source
BILF24T26	24"	26	Compact Fluorescent
BILF24T32	24"	32	Compact Fluorescent
BILF24T42	24"	42	Compact Fluorescent
BILF2450H	24"	50	HPS
BILF2470H	24"	70	HPS
BILF2439M	24"	39	MH
BILF2450M	24"	50	MH
BILF2470M	24"	70	MH
BILF36T26	36"	26	Compact Fluorescent
BILF36T32	36"	32	Compact Fluorescent
BILF36T42	36"	42	Compact Fluorescent
BILF3650H	36"	50	HPS
BILF3670H	36"	70	HPS
BILF3639M	36"	39	MH
BILF3650M	36"	50	MH
BILF3670M	36"	70	MH
BILF42T26	42"	26	Compact Fluorescent
BILF42T32	42"	32	Compact Fluorescent
BILF42T42	42"	42	Compact Fluorescent
BILF4250H	42"	50	HPS
BILF4270H	42"	70	HPS
BILF4239M	42"	39	MH
BILF4250M	42"	50	MH
BILF4270M	42"	70	MH

