

# Lumen Tech

Lighting, LLC.

## Design F235

Adjustable Swivel Mount Flood Light  
Maximum 175W Metal Halide  
150W High Pressure Sodium  
Or 42W PLT Compact Fluorescent

### Specifications

**Housing:** Heavy duty cast aluminum with silicone gasket. Powder coated finish. See finish note.

**Lens:** Clear tempered glass silicone sealed to door frame.

**Reflector:** Anodized aluminum, computer designed for efficiency.

**Ballast: H.I.D.:** Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF:** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

**Lamp: H.I.D.:** Clear medium base. **CF:** PLT lamp, 4 pin base (by others).

**Lamp Holder: H.I.D.:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** white thermoplastic with snap-in lamp retainer springs.

**Finish:** Bronze, detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

**Photometric Information:** Contact factory.

**Labels:** U/L, CUL listed suitable for wet location.

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE*

### Ordering Information

Catalog Number	Watts	Light Source
F235T26	26	Compact Fluorescent
F235T32	32	Compact Fluorescent
F235T42	42	Compact Fluorescent
F23570H	70	HPS
F235100H	100	HPS
F235150H	150	HPS
F23570M	70	MH
F235100M	100	MH
F235150M	150	MH
F235175M	175	MH

### Optional Mounting Plate F235MP

