

Lumen Tech

Lighting, LLC.

Design PM22A Arm Mount Area Light Maximum 1000W Metal Halide Or High Pressure Sodium

Specifications

Housing: Die cast aluminum construction with corrosion resistant hardware. Extruded aluminum arm for pole mounting. See finish note.

Door Frame: Die cast aluminum, one piece silicone gasket, seals door frame to housing. See finish note.

Lens: Impact resistant clear tempered glass, silicone caulked to door frame.

Reflector: Anodized aluminum, designed for maximum efficiency, type III distribution.

Ballast: Pre-wired C.W.A., H.P.F. core and coil with capacitor.

Lamp: Clear mogul base, (by others).

Lamp Holder: High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact.

Finish: Dark Bronze, detergent cleaned, prime coated. Chip resistant powder urethane polyester coating.

Photometric Information: Contact factory.

Labels: U/L, CUL listed suitable for wet location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



Ordering Information

Catalog Number	Watts	Light Source
PM22A250H	250	HPS
PM22A400H	400	HPS
PM22A1000H	1000	HPS
PM22A250M	250	MH
PM22A400M	400	MH
PM22A400MP	400	MH PS
PM22A1000M	1000	MH

Options & Accessories



PM22ASH
Polycarbonate Shield

PM22AWG
Wire Guard

PM22AV
Visor Shield

