

# Lumen Tech

Lighting, LLC.

## Design QBICD

7" Diameter 32" or 44" Tall Dome Top Bollard  
Polycarbonate Lens With Internal Cone Reflector

### Specifications

**Housing:** Aluminum 7" diameter, fastened to a cast aluminum base with three countersunk stainless steel screws. See finish note.

**Housing Top:** Spun aluminum 7" diameter with a dome top. Finished same as housing.

**Base:** Cast aluminum, finished same as housing. See finish note.

**Lens:** Injection molded, 7" diameter, 1/4" thick clear polycarbonate.

**Ballast:** **H.I.D.** Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

**Lamp:** **H.I.D.** Clear medium base. **CF** PLT lamp max. 42W, 4 pin base (by others).

**Lamp Holder:** **H.I.D.:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** White thermoplastic with snap-in lamp retainer springs.

**Finish:** Black, white, or bronze detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

**Photometric Information:** Contact factory.

**Labels:** U/L listed. IP65 Suitable for wet location.

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE*



Anchor bolt and installation bracket kit. Order catalog number **AB8**.

### Ordering Information

Catalog Number	Height	Watts	Light Source
QBICD32T26	32"	26	Compact Fluorescent
QBICD32T32	32"	32	Compact Fluorescent
QBICD32T42	32"	42	Compact Fluorescent
QBICD3250H	32"	50	HPS
QBICD3270H	32"	70	HPS
QBICD32100H	32"	100	HPS
QBICD3239M	32"	39	MH
QBICD3250M	32"	50	MH
QBICD3270M	32"	70	MH
QBICD32100M	32"	100	MH
QBICD42T26	44"	26	Compact Fluorescent
QBICD42T32	44"	32	Compact Fluorescent
QBICD42T42	44"	42	Compact Fluorescent
QBICD4250H	44"	50	HPS
QBICD4270H	44"	70	HPS
QBICD42100H	44"	100	HPS
QBICD4239M	44"	39	MH
QBICD4250M	44"	50	MH
QBICD4270M	44"	70	MH
QBICD42100M	44"	100	MH