

# Lumen Tech

Lighting, LLC.

## Design QBIRD

7" Diameter 32" or 44" Tall Dome Top Bollard  
Polycarbonate Lens With Internal Glass Refractor

### Specifications

**Housing:** Aluminum 7" diameter, fastened to a cast aluminum base with three countersunk stainless steel screws. See finish note.

**Housing Top:** Spun aluminum 7" diameter with a dome top. Finished same as housing.

**Base:** Cast aluminum, finished same as housing. See finish note.

**Lens:** Injection molded, 7" diameter, 1/4" thick clear polycarbonate.

**Ballast:** **H.I.D.** Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

**Lamp:** **H.I.D.** Clear medium base. **CF** PLT lamp max. 42W, 4 pin base (by others).

**Lamp Holder:** **H.I.D.:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** White thermoplastic with snap-in lamp retainer springs.

**Finish:** Black, white, or bronze detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

**Photometric Information:** Contact factory.

**Labels:** U/L listed. IP65 Suitable for wet location.

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE*



Anchor bolt and installation bracket kit. Order catalog number **AB8**.

### Ordering Information

Catalog Number	Height	Watts	Light Source
QBIRD32T26	32"	26	Compact Fluorescent
QBIRD32T32	32"	32	Compact Fluorescent
QBIRD32T42	32"	42	Compact Fluorescent
QBIRD3250H	32"	50	HPS
QBIRD3270H	32"	70	HPS
QBIRD32100H	32"	100	HPS
QBIRD3239M	32"	39	MH
QBIRD3250M	32"	50	MH
QBIRD3270M	32"	70	MH
QBIRD32100M	32"	100	MH
QBIRD42T26	44"	26	Compact Fluorescent
QBIRD42T32	44"	32	Compact Fluorescent
QBIRD42T42	44"	42	Compact Fluorescent
QBIRD4250H	44"	50	HPS
QBIRD4270H	44"	70	HPS
QBIRD42100H	44"	100	HPS
QBIRD4239M	44"	39	MH
QBIRD4250M	44"	50	MH
QBIRD4270M	44"	70	MH
QBIRD42100M	44"	100	MH