

Lumen Tech

Lighting, LLC.

Design QBIRF

7" Diameter 32" or 44" Tall Flat Top Bollard
Polycarbonate Lens With Internal Glass Refractor

Specifications

Housing: Aluminum 7" diameter, fastened to a cast aluminum base with three countersunk stainless steel screws. See finish note.

Housing Top: Spun aluminum 7" diameter with a flat top. Finished same as housing.

Base: Cast aluminum, finished same as housing. See finish note.

Lens: Injection molded, 7" diameter, 1/4" thick clear polycarbonate.

Ballast: **H.I.D.** Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

Lamp: **H.I.D.** Clear medium base. **CF** PLT lamp max. 42W, 4 pin base (by others).

Lamp Holder: **H.I.D.:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** White thermoplastic with snap-in lamp retainer springs.

Finish: Black, white, or bronze detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

Photometric Information: Contact factory.

Labels: U/L listed. IP65 Suitable for wet location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



Anchor bolt and installation bracket kit. Order catalog number **AB8**.

Ordering Information

Catalog Number	Height	Watts	Light Source
QBIRF32T26	32"	26	Compact Fluorescent
QBIRF32T32	32"	32	Compact Fluorescent
QBIRF32T42	32"	42	Compact Fluorescent
QBIRF3250H	32"	50	HPS
QBIRF3270H	32"	70	HPS
QBIRF32100H	32"	100	HPS
QBIRF3239M	32"	39	MH
QBIRF3250M	32"	50	MH
QBIRF3270M	32"	70	MH
QBIRF32100M	32"	100	MH
QBIRF42T26	44"	26	Compact Fluorescent
QBIRF42T32	44"	32	Compact Fluorescent
QBIRF42T42	44"	42	Compact Fluorescent
QBIRF4250H	44"	50	HPS
QBIRF4270H	44"	70	HPS
QBIRF42100H	44"	100	HPS
QBIRF4239M	44"	39	MH
QBIRF4250M	44"	50	MH
QBIRF4270M	44"	70	MH
QBIRF42100M	44"	100	MH