

Lumen Tech

Lighting, LLC.

Design QSC35/36 Wall Sconce With Down or Up Down Light Maximum 175W Metal Halide 150W High Pressure Sodium Or 2-42W PLT Compact Fluorescent

Specifications

Housing: Heavy duty die-cast aluminum with quick mount system. Powder coated finish. See finish note.

Lens: Clear tempered glass silicone sealed to door frame.

Reflector: Anodized aluminum, computer designed for efficiency, classified type IV.

Ballast: H.I.D.: Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF:** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

Lamp: H.I.D.: Clear medium base. **CF:** PLT lamp max. 2-42W, 4 pin base (by others).

Lamp Holder: H.I.D.: High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact.

CF: White thermoplastic with snap-in lamp retainer springs.

Finish: White, black or bronze, detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for custom colors.

Photometric Information: Contact factory.

Labels: U/L listed suitable for wet location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



QSC35 Down
Light Only



QSC36
UP/Down Light

Ordering Information Down Light

Catalog Number	Watts	Light Source
QSC35T26	1-26	Compact Fluorescent
QSC35T32	1-32	Compact Fluorescent
QSC35T42	1-42	Compact Fluorescent
QSC352T26	2-26	Compact Fluorescent
QSC352T32	2-32	Compact Fluorescent
QSC352T42	2-42	Compact Fluorescent
QSC3570H	70	HPS
QSC35100H	100	HPS
QSC35150H	150	HPS
QSC3570M	70	MH
QSC35100M	100	MH
QSC35150M	150	MH
QSC35175M	175	MH

Ordering Information Up / Down Light

QSC36T26	1-26	Compact Fluorescent
QSC36T32	1-32	Compact Fluorescent
QSC36T42	1-42	Compact Fluorescent
QSC362T26	2-26	Compact Fluorescent
QSC362T32	2-32	Compact Fluorescent
QSC362T42	2-42	Compact Fluorescent
QSC3670H	70	HPS
QSC36100H	100	HPS
QSC36150H	150	HPS
QSC3670M	70	MH
QSC36100M	100	MH
QSC36150M	150	MH
QSC36175M	175	MH

