

# Lumen Tech

Lighting, LLC.

## Design SC302

Surface Mount Wall Sconce With Up Light  
Maximum 175W Metal Halide  
150W High Pressure Sodium  
Or 32W PLT Compact Fluorescent

### Specifications

**Housing:** Heavy duty cast aluminum with quick mount system. Powder coated finish. See finish note.

**Lens:** Clear tempered glass silicone sealed to door frame.

**Reflector:** Anodized aluminum, computer designed for efficiency, classified type III.

**Ballast: H.I.D.:** Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF:** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

**Lamp: H.I.D.:** Clear medium base. **CF:** PLT lamp max. 32W, 4 pin base (by others).

**Lamp Holder: H.I.D.:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact.


**CF:** White thermoplastic with snap-in lamp retainer springs.

**Finish:** Bronze, detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

**Photometric Information:** Contact factory.

**Labels:** U/L, CUL listed suitable for wet location.

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE*



### Ordering Information

Catalog Number	Watts	Light Source
SC302T26	26	Compact Fluorescent
SC302T32	32	Compact Fluorescent
SC30270H	70	HPS
SC302100H	100	HPS
SC302150H	150	HPS
SC30270M	70	MH
SC302100M	100	MH
SC302150M	150	MH
SC302175M	175	MH

### Quick Mount System

