

Lumen Tech

Lighting, LLC.

Design SC34 Wall Sconce With Up/Down Or Full Cut Off Down Light Maximum 100W Metal Halide 150W High Pressure Sodium Or 2-42W PLT Compact Fluorescent

Specifications

Housing: Heavy duty die-cast aluminum with quick mount system. Powder coated finish. See finish note.

Lens: Clear tempered glass silicone sealed to lens frame.

Reflector: Anodized aluminum, computer designed for efficiency, up/down distribution. Features an internal baffle to block up light for full cut off down light only.

Ballast: **H.I.D.:** Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF:** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

Lamp: **H.I.D.:** Clear medium base. **CF:** PLT lamp 4 pin base (by others).

Lamp Holder: **H.I.D.:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact.

CF: White thermoplastic with snap-in lamp retainer springs.

Finish: White, black or bronze, detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

Photometric Information: Contact factory.

Labels: U/L, listed suitable for wet location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



Ordering Information

Catalog Number	Watts	Light Source
SC34T26	1-26	Compact Fluorescent
SC34T32	1-32	Compact Fluorescent
SC34T32	1-32	Compact Fluorescent
SC34T226	2-26	Compact Fluorescent
SC34T232	2-32	Compact Fluorescent
SC34T242	2-42	Compact Fluorescent
SC3450H	50	HPS
SC3470H	70	HPS
SC34100H	100	HPS
SC34150H	150	HPS
SC3439M	39	MH
SC3450M	50	MH
SC3470M	70	MH
SC34100M	100	MH