

Lumen Tech

Lighting, LLC.

Design VWD Oval Wall Mount Up / Down Light Cylinder

Specifications

Cylinder: Oval extruded aluminum cylinder, hinged die-cast ballast compartment with safety cable. See finish note.

Mounting Bracket: Unique wall mount bracket for quick and easy installation.

Lens: Clear tempered glass lens silicone caulked to lens frame.

Reflector: Anodized aluminum reflector computer designed for maximum efficiency.

Ballast: **H.I.D.** Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

Lamp: **H.I.D.** Clear medium base. **CF** PLT lamp max. 2-42W, 4 pin base (by others).

Lamp Holder: H.I.D.: High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** White thermoplastic with snap-in lamp retainer springs.

Finish: White, black or bronze detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

Photometric Information: Contact factory.

Labels: U/L listed. Suitable for wet location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



Ordering Information

| Catalog Number | Watts | Light Source |
|----------------|-------|---------------------|
| VWDT26 | 1-26 | Compact Fluorescent |
| VWDT32 | 1-32 | Compact Fluorescent |
| VWDT42 | 1-42 | Compact Fluorescent |
| VWDT226 | 2-26 | Compact Fluorescent |
| VWDT232 | 2-32 | Compact Fluorescent |
| VWDT242 | 2-42 | Compact Fluorescent |
| VWD50H | 50 | HPS |
| VWD70H | 70 | HPS |
| VWD100H | 100 | HPS |
| VWD150H | 150 | HPS |
| VWD39M | 39 | MH |
| VWD50M | 50 | MH |
| VWD70M | 70 | MH |
| VWD100M | 100 | MH |
| VWD150M | 150 | MH |
| VWD175M | 175 | MH |

Dimensions

