

# Lumen Tech

Lighting, LLC.

## Design WBF

7" Diameter 15-5/8" Tall Flat Top Wall Mount Bollard  
Polycarbonate Lens With Internal Glass Refractor,  
Cone Reflector or Louver

### Ordering Information

Catalog Number	Watts	Light Source
<b>Internal Glass Refractor</b>		
WBIRFT26	26	Compact Fluorescent
WBIRFT32	32	Compact Fluorescent
WBIRFT42	42	Compact Fluorescent
WBIRF50H	50	HPS
WBIRF70H	70	HPS
WBIRF100H	100	HPS
WBIRF39M	39	MH
WBIRF50M	50	MH
WBIRF70M	70	MH
WBIRF100M	100	MH



WBIRF Internal Glass Refractor



WBICF Internal Cone Reflector

### Internal Cone Reflector

WBICFT26	26	Compact Fluorescent
WBICFT32	32	Compact Fluorescent
WBICFT42	42	Compact Fluorescent
WBICF50H	50	HPS
WBICF70H	70	HPS
WBICF100H	100	HPS
WBICF39M	39	MH
WBICF50M	50	MH
WBICF70M	70	MH
WBICF100M	100	MH



WBILF Internal Louver

### Internal Louver

WBILFT26	26	Compact Fluorescent
WBILFT32	32	Compact Fluorescent
WBILFT42	42	Compact Fluorescent
WBILF50H	50	HPS
WBILF70H	70	HPS
WBILF100H	100	HPS
WBILF39M	39	MH
WBILF50M	50	MH
WBILF70M	70	MH
WBILF100M	100	MH

### Specifications

**Housing:** 7" Diameter extruded aluminum with internal ballast tray for easy maintenance. See finish note.

**Housing Top:** Spun aluminum 7" diameter with a flat top. Finished same as housing.

**Wall Mount:** Cast aluminum with quick mount bracket, finished same as housing. See finish note.

**Lens:** Injection molded, 7" diameter, 1/4" thick clear polycarbonate.

**Ballast:** **H.I.D.** Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

**Lamp:** **H.I.D.** Clear medium base. **CF** PLT lamp max. 42W, 4 pin base (by others).

**Lamp Holder:** **H.I.D.:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** White thermoplastic with snap-in lamp retainer springs.

**Finish:** Black, white, or bronze detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

**Photometric Information:** Contact factory.

**Labels:** U/L listed. Suitable for wet location.

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE*

### Cat.# BOLPC

Polycarbonate replacement lens fits all 7" diameter bollards

