

Lumen Tech

Lighting, LLC.

Design WP716

Surface Mount Wall Pack

Maximum 50 Watt Metal Halide

50W High Pressure Sodium

Or 42W PL Compact Fluorescent

With 1/2" Hole For Optional Photo Cell

Specifications

Housing: High impact polycarbonate lens and housing finished bronze.

Reflector: Anodized aluminum, computer designed in conjunction with the lens for efficiency.

Ballast HID: Pre-wired H.P.F. core and coil with capacitor. **CF:** Compact fluorescent electronic high power factor class P, universal voltage 120V—277V 50 / 60 Hz.

Lamp HID: Clear medium base lamp. **CF:** PLT lamp 4 pin base. (by others).

Lamp Holder HID: High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** White thermoplastic with snap-in lamp retainer springs.

Photometric Information: Contact factory.

Labels: U/L, listed suitable for wet location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



WP716 Down Light



WP716CO Cut Off



WP716UD Up / Down Light

Ordering Information

Catalog Number	Watts	Light Source
Down Light		
WP716PLT26	PLT26	Compact Fluorescent
WP716PLT32	PLT32	Compact Fluorescent
WP716PLT42	PLT42	Compact Fluorescent
WP71650H	50	HPS
WP71650M	50	MH

Cut Off (Dark Sky Compliant)

WP716COPLT26	PLT26	Compact Fluorescent
WP716COPLT32	PLT32	Compact Fluorescent
WP716COPLT42	PLT42	Compact Fluorescent
WP716CO50H	50	HPS
WP716CO50M	50	MH

Up / Down Light

WP716UDPLT26	PLT26	Compact Fluorescent
WP716UDPLT32	PLT32	Compact Fluorescent
WP716UDPLT42	PLT42	Compact Fluorescent
WP716UD50H	50	HPS
WP716UD50M	50	MH

