

Lumen Tech

Lighting, LLC.

Design WPRF

15" Diameter Architectural Surface Mount
White Frosted Glass Lens
Open, 1/2 Circle or Grid Frame Aperture

Ordering Information

Catalog Number	Watts	Light Source
Full Circle White Frosted Glass Lens		
WPRFCFT26	26	Compact Fluorescent
WPRFCFT32	32	Compact Fluorescent
WPRFCFT42	42	Compact Fluorescent
WPRFCFT226	2-26	Compact Fluorescent
WPRFCFT232	2-32	Compact Fluorescent
WPRFCFT242	2-42	Compact Fluorescent
WPRFCF50H	50	HPS
WPRFCF70H	70	HPS
WPRFCF100H	100	HPS
WPRFCF150H	150	HPS
WPRFCF39M	39	MH
WPRFCF50M	50	MH
WPRFCF70M	70	MH
WPRFCF100M	100	MH
WPRFCF150M	150	MH
WPRFCF175M	175	MH

1/2 Circle White Frosted Glass Lens

WPRHCFT26	26	Compact Fluorescent
WPRHCFT32	32	Compact Fluorescent
WPRHCFT42	42	Compact Fluorescent
WPRHCFT226	2-26	Compact Fluorescent
WPRHCFT232	2-32	Compact Fluorescent
WPRHCFT242	2-42	Compact Fluorescent
WPRHCF50H	50	HPS
WPRHCF70H	70	HPS
WPRHCF100H	100	HPS
WPRHCF150H	150	HPS
WPRHCF39M	39	MH
WPRHCF50M	50	MH
WPRHCF70M	70	MH
WPRHCF100M	100	MH
WPRHCF150M	150	MH
WPRHCF175M	175	MH

Frosted Glass Lens With Decorative Grid Frame

WPRGRFT26	26	Compact Fluorescent
WPRGRFT32	32	Compact Fluorescent
WPRGRFT42	42	Compact Fluorescent
WPRGRFT226	2-26	Compact Fluorescent
WPRGRFT232	2-32	Compact Fluorescent
WPRGRFT242	2-42	Compact Fluorescent
WPRGRF50H	50	HPS
WPRGRF70H	70	HPS
WPRGRF100H	100	HPS
WPRGRF150H	150	HPS
WPRGRF39M	39	MH
WPRGRF50M	50	MH
WPRGRF70M	70	MH
WPRGRF100M	100	MH
WPRGRF150M	150	MH
WPRGRF175M	175	MH



WPRFCC Full circle white frosted glass lens.



WPRGRC White frosted glass lens with decorative grid frame.



WPRHCC 1/2 Circle white frosted glass lens.

Specifications

Housing: 15" Diameter aluminum die-cast housing with coin plugs on sides and back, built in template for mounting to electrical box. See finish note.

Lens: Molded white frosted glass lens with open, 1/2 cut off or grid style frame. See finish note.

Ballast: **H.I.D.** Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

Lamp: **H.I.D.** Clear medium base. **CF** PLT lamp, 4 pin base (by others).

Lamp Holder: **H.I.D.:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** White thermoplastic with snap-in lamp retainer springs.

Finish: Black, white, or bronze detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

Photometric Information: Contact factory.

Labels: U/L listed. Suitable for wet location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE